

**General Description:**

Dust-X is a cationic based emulsion formulated to control fugitive dust emissions. Dust-X is an environmentally friendly material specialized for unpaved road applications. The product works by bonding dust and aggregate particles together resembling a paved surface that has superior load bearing qualities. Treating an unpaved road with Dust-X will prevent problems such as erosion, dust containment, and wet weather damage that typically overwhelm rural areas.

**Directions:**

1. Apply with water via distributor truck according to the guide line below

2. Allow Dust-X to fully cure before opening the road to any traffic

1<sup>st</sup> Application-1 part Dust-x to 7-8 parts water

2<sup>nd</sup> Application-2 weeks later 1 part Dust-X to 5-7 parts water

3<sup>rd</sup> Application-1-3 months later, 1 part Dust-X to 3-5 parts water

4<sup>th</sup> Application-4-9 months later, 1 part Dust-X to 3-5 parts water

5<sup>th</sup> Application-12 months or as needed due to traffic 1 part Dust-X to 3-5 parts water

\*After this process you will have a stable base for a final surface treatment when desired.



**DUST-X**



Manufactured By:

Professional Coating Technologies Inc  
1001 Mt Lebanon Rd  
Cedar Hill TX.75014  
972.291.7474  
[www.pctworldwide.com](http://www.pctworldwide.com)

*PCT Inc, an environmentally friendly company*