



# PCT

Professional Coating  
Technologies, Inc.

# PHPM-50

WE PROTECT YOUR WATER

## **General Description:**

PHPM-50 is an environmentally friendly alternative for pothole tack. It features a non-tracking membrane that is applied to the bottom, sides and finished surface of potholes. Our PHPM-50 is composed of a liquid Geo-Tech membrane that not only extends the life of the patch, but also promotes adhesion for the patch mix and the existing surface. PHPM-50 is easily applied by spray on or broom on methods and is compatible with both cold and hot mix patching methods.



## **Directions:**

1. Thoroughly clean and remove any debris and or water from the pothole.
2. Cut the sides of the pothole with a pavement saw to square the hole.
3. Clean the pothole once again.
4. Apply the PHPM-50 to the bottom and sides of the pothole. Overlap the top edges at least 2 inches.
5. Fill the pothole with the patching mix and compact with desired compaction method.
6. Once the patch is compacted, apply the final coat of PHPM-50 to the finished surface. Extend material at least 4 inches beyond patch edge.
7. Allow 5 minutes for drying time. Do not use in the rain!

Manufactured By:

Professional Coating Technologies Inc  
1001 Mt Lebanon Rd  
Cedar Hill TX.75014  
972.291.7474  
[www.pctworldwide.com](http://www.pctworldwide.com)

*PCT Inc, an environmentally friendly  
company*

*Earth Friendly Products*